

In-line O₂ Gehaltemeter

Norit
Haffmans

In-line O₂ Gehaltemeter
OGM



In-line O₂ Gehaltemeter

General product information

In the wine, beer and beverage industries, the content of dissolved oxygen (DO) is extremely important to both product quality and taste. Excess oxygen (O₂) can compromise the flavor stability and lead to significantly reduced product shelf life. Because of this, wineries, breweries and other beverage manufacturers continuously seek to measure and control the O₂ concentrations throughout production.

The In-line O₂ Gehaltemeter, type OGM, combines high accuracy with excellent measurement stability. This new optical O₂ measurement technology provides better response times than traditional O₂ measuring devices, and does not require frequent calibration.

The OGM is available in two measuring ranges:

- Low measuring range (LHO) for accurate DO measurement of beverages < 2,000 ppb
- Wide measuring range (WLO) for accurate DO measurement of beverages < 45.0 ppm

The OGM can be installed anywhere in the production process where the determination of the dissolved oxygen content is critical to the quality of the product. The O₂ probe is hygienically designed, and is easily mounted. It is available in two executions:

- Varivent connection
- 25 mm connection that will fit in a classic 25 mm sensor connection

OGM

In-line O₂ Gehaltemeter



Varivent probe



25 mm probe

Benefits

- Accurate process control
 - measurement data storage
- Cost saving
 - no product loss
 - low maintenance

Application

- In-line, at critical locations in the production line where the determination of the dissolved O₂ content is required and adjustments within the process can be made

Technical Data

Control Unit

Power supply	85 - 264 VAC wide range (optional 24 VDC)
Dimensions	ca. 8x8x3 in. (LxWxH)
Mounting	wall mounting/panel mounting

O₂ probe

Process connection	Varivent	25 mm
Dimensions	ca. 8x4 in. (LxW)	ca. 11x4 in. (LxW)

O₂ sensor

Type	LHO	WLO
Measuring range	0.0 - 2,000 ppb	0.0 to 45 ppm
Accuracy	± 1 ppb + 2% of m.v.	< 5% of m.v.

Measuring units	ppb, ppm
Temperature	23 - 104° F, acc. ± 0.1° F
Measuring interval	30 sec. (adjustable from 2 - 999 sec.)
Memory capacity	up to 500 measurements
Weight	ca. 11 lbs.

Scope of Supply

- Control unit
- Wall mounting set
- O₂ probe
- Main cable
- Probe communication cable
- I/O cable for analog output
- Calibration set with spare O-ring
- Instruction manual

Options

- Pipe/probe mounting set
- In-line varivent clamp
- Software (CD + RS cable)
- Profibus DP
- In-line housing with varivent connection
- O₂ calibration set
- Certificate of measurement

Haffmans North America, Inc. reserves the right to make changes in the technical specifications at any time.



Haffmans North America, Inc.

1330 Anvil Drive, Rockford, IL 61115 USA

T 815.639.0322 • F 815.639.1135

E info@haffmansna.com • I www.haffmansna.com

Norit
leading in purification

Haffmans

OGM